



Shown: CRPP60

Specifications:

- Max Load.....3000 lbs (1360.8)
- Piston Thrust (At 8 psi).....*2261 lbs (1025 kgs)
- Auto Center Option.....Yes
- Sensor Bracket Style.....104
- Temperature.....32 - 350° F (0 - 66° C)
- Air Consumption (At 8 psi).....2.4 CFM (68 l/m)

Requirements:

- Existing guide must be in good mechanical condition and move freely (without bind).
- Guide must be properly located and installed on a web processing machine.
- The air-flow (edge) sensor must be securely mounted after the guide’s exit roller and within the first one-third of the exit span.
- It may be necessary to relocate the existing guide to obtain desired guiding results.

BRP & CRP P50

Retrofit Kit

The BRP (Basic Retrofit Package) and CRP (Complete Retrofit Package) is a basic system with or without a raceway. It is designed to attach directly to an existing steering guide, displacement guide and some miscellaneous equipment like the Arpeco Tracker. The sensor mounts independent of the stand (after the last shifting idler) and does not move. This compact guiding assembly is ideally suited for new machines as well as retrofits (upgrade) on older machines. No electronics, No hydraulics means no problems. The Retrofit Package is easy to install and setup.

Environment Applications:

- Wash down
- High Heat
- High Humidity
- Dusty Dirty
- Clean Room
- Explosion Proof

How To Specify:

CRPP50

Retrofit Package Ø5 in. Cylinder
 C - Complete
 B - Basic
 AT - Arpeco Tracker

Equipment Included:

- Servo Controller
- Two-Stage Canister/Coalescing Air Filter
- Precision Air Regulator With Gauge
- Air Cylinder
- Raceway/Carrier Block Assembly (CRP)
- Auto Center Sensor Bracket (Optional)
- 3-Way Valve (Optional)
- 12in. (305) Threaded Rod
- Connector Bracket
- 30ft. (9.1m) of Ø.25in. (6.35) Polyurethane Air Hose

Additional Optional Equipment:

- Center Guide
- Remote Sensor Controls
- Stainless Steel



Shown: BRPP50